

500 - NOM

AIR RELIEF VALVE ASSEMBLY - TYPE 1 (CoA 618)

DESCRIPTION DATE **CONSTRUCTION STANDARDS** ORIGINAL ISSUE 07/22 **LANDSCAPE IRRIGATION**

AIR RELIEF VALVE ASSEMBLY - TYPE 1 - DRIP IRRIGATION FOR GARDEN BEDS & TREE RINGS

GENERAL NOTES:

- ALL VALVES TO BE INSTALLED TO ALLOW EASE OF MAINTENANCE WITHOUT HAVING TO REMOVE THE VALVE BOX.
- THE CONTRACTOR SHALL CAREFULLY STUDY AND COMPARE ALL DRAWINGS, SPECIFICATIONS AND OTHER INSTRUCTIONS. CONTRACTOR TO NOTIFY IN WRITING THE CITY OF ADELAIDE OF ANY DISCREPANCIES BETWEEN THE PROJECT DRAWINGS AND STANDARD DETAILS FOR CLARIFICATION PRIOR TO UNDERTAKING THE WORKS.
- AIR RELIEF VALVE MAY BE LOCATED ALONG FLUSH PIPE, WITHIN GARDEN BED (PREFERRED) OR WITHIN 500mm OF GARDEN BED EDGING/EXTENT - ENSURE AT HIGHEST POINT.
- SITE CHECK CONDITIONS & CONFIRM WITH CoA IRRIGATION TECHNICAL OFFICER.

APPLICATION:

 ALL DRIP (GARDEN BED) IRRIGATION SYSTEMS AT HIGH POINT.

KEYNOTE LEGEND

- 1. BERMAD 1 INCH AIR RELEASE VALVE/ VACUUM BREAKER
- RAINBIRD VB SERIES VALVE BOX 150mm ROUND
- HIGH DENSITY PLASTIC SHEETING (200uM)
- EXISTING SPOIL RE-COMPACTED AROUND BOX
- **RE-LAID EXISTING SOD-CUT TURF**
- 20mm WASHED BLUE METAL GRAVEL BASE
- 50mm HIGH MASONRY PAVER
- 25mm LDPE FLUSH PIPE
- LDPE THREADED ELBOW 15mm FEMALE THREAD TO 25mm MALE BARBED END
- 10. RESERVED
- 11. STAINLESS STEEL 'COBRA' CLIPS
- 12. LDPE BARBED REDUCING TEE 25 x 13mm
- 13. 75mm HIGH CoA PARK LAND MULCH
- 14. LDPE DRIP LINE
- 15. LDPE RISER/DROPPER WITH 25mm SINGLE BARBED LDPE ELBOW CONNECTORS, TOP & BOTTOM
- 16. LDPE ELBOW CONNECTOR 25mm TO 25mm SINGLE BARB ENDS
- 17. 13mm NETAFIM ASPC TECHLINE DRIP LINE. REFER TO CoA 629 FOR EMITTER & DRIP LINE SPACINGS.



LS019