

M10x45 LONG HEX BOLT
THROUGH LOWER STRAP.
WELD HEAD AT BACK OF
STRAP. COMPLETE WITH
2 GALVANIZED NUTS.

Diagram illustrating the rear of the access cover with the following labels:

- PROVIDE FIXING AND LANYARD FOR ACCESS COVER
- LABEL BEHIND COVER FIXED TO GEAR TRAY
- 7mm HOLE TO SUIT M6 ALLEN KEY SOCKET HD CAP SCREW PROVIDE NYLON WASHER, DIAMETER SAME SIZE AS SCREW HEAD

NOTES:

1. COLUMN TO CONFORM TO RELEVANT AUSTRALIAN STANDARDS AND ATTACHED CoA SPECIFICATION.
2. COLUMN SHALL BE HOT DIPPED GALVANISED.
3. FOR FOOTING DETAILS REFER TO STANDARD CoA 810.
4. LABEL REQUIREMENTS:

CORPORATION OF THE CITY OF ADELAIDE
MANUFACTURER'S NAME
CONTRACT NUMBER
MONTH/YEAR OF MANUFACTURE


CoA 811 6.5m COLUMN

REV	DESCRIPTION	DATE
A	ORIGINAL ISSUE	10/22

CONSTRUCTION STANDARD

LIGHTING & ELECTRICAL

6.5m COLUMN



SHEET NUMBER
LE011
REVISION
A